



(43) International Publication Date
24 November 2005 (24.11.2005)

PCT

(10) International Publication Number
WO 2005/110535 A1


- (51) **International Patent Classification⁷:** **A61N 1/37,**
1/365, A61B 5/021
- (21) **International Application Number:**
PCT/SE2004/000741
- (22) **International Filing Date:** 13 May 2004 (13.05.2004)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (71) **Applicant (for all designated States except US):** **ST JUDE MEDICAL AB** [SE/SE]; .. S-175 84 JÄRFÄLLA (SE).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** **HEDBERG, Sven-Erik** [SE/SE]; .. Odonstigen 5, S-196 32 KUNGSÅNGEN (SE). **BJÖRLING, Anders** [SE/SE]; .. Handbollsvägen 24 G, S-175 53 JÄRFÄLLA (SE). **TORPO, Maria** [SE/SE]; .. Duvkullavägen 42 B, S-172 37 SUNDBYBERG (SE). **LJUNGSTRÖM, Karin** [SE/SE]; .. Albert Landbergs gränd 34, S-165 70 HÄSELBY (SE).
- (74) **Agents:** **HOPFGARTEN, Nils** et al.; Groth & Co. KB, Box 6107, S-102 32 Stockholm (SE).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declarations under Rule 4.17:**
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE,

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE,

[Continued on next page]

- (54) Title:** DETECTION OF DIASTOLIC HEART FAILURE



(57) Abstract: An implantable medical apparatus for detecting diastolic heart failure, DHF, comprises a DHF determining device for determining at least one blood pressure parameter for detecting a DHF state of the heart (4) of a patient. The DHF determining device comprises a pressure measuring means (2,26) for measuring the absolute value of left atrial pressure during the diastasis phase just before atrial contraction, or the absolute value of the pressure in the pulmonary vein when the pulmonary valve is closed, for a predetermined workload situation and a rest situation of the patient. A comparison means (18) compares the difference between left atrial pressure or pulmonary vein pressure, in said workload and rest situations, with a predetermined pressure difference reference value. A pacemaker comprises such an apparatus and control means (14) for optimising pacing therapy depending on the result of the comparisons with the reference values. A corresponding method of detecting diastolic heart failure, DHF, comprises the step of determining at least one blood pressure parameter for detecting a DHF state of the heart of a patient. The absolute value of left atrial pressure is measured during the diastasis phase just before atrial contraction, or the absolute value of the pressure in the pulmonary vein when the pulmonary valve is closed, for a predetermined workload situation and a rest situation of the patient. The difference between left atrial pressure or pulmonary vein pressure in said workload and rest situations is compared with a predetermined pressure difference reference value.



EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE,

IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.